


JT360-380SIh(B)

Dual-glass Monocrystalline Solar Module

120 Cells / MBB / Bifacial Mono PERC / 1500V DC / 20.5% Maximum Efficiency



KEY FEATURES



Ultra-high power output
 MBB mono PERC cell technology, maximum power output 380W
 Half-cut cell layout, lower Rs loss and thermal coefficients
 Bifacial cell, additional 5%-30% more yield



Excellent low light performance
 Excellent low light performance on cloudy days
 mornings and evenings



Certified to withstand the most challenging environment
 2400 Pa wind load • 5400 Pa snow load • 25 mm hail stones at 82 km/h



High system voltage Compatible
 Maximum 1500V DC system voltage saves total system cost



High fire class
 Fire class C certified, minimize the fire risk of the system

QUALIFICATIONS & CERTIFICATES

- IEC 61215, IEC 61730
- ISO 9001: Quality Management System
- ISO 14001: Environment Management System
- OHSAS 18001: Occupational Health and Safety

WARRANTY



12 years Product Warranty



15 years Product Warranty




30 years Performance Warranty

* Applies to rooftop market in Australia only.


JETION SOLAR

As a member of CNBM - a Fortune 500 company, Jetion Solar provides various product solutions, global EPC service and financing. Its standard and high-efficiency product offerings are among the most powerful and cost-effective in the industry. Till now, Jetion Solar has cumulatively more than 10 GW module shipment and 1 GW global EPC track records.




IV CURVES

IV Curves of JT360SIh(B) at different irradiances



IV Curves of JT360SIh(B) at different Temp



ELECTRICAL DATA

	JT360 SIh(B)	JT365 SIh(B)	JT370 SIh(B)	JT375 SIh(B)	JT380 SIh(B)
Test Condition	STC	STC	STC	STC	STC
Maximum Power Pmax (W) <small>(tolerance±3%) (selection limits-0/+5W)</small>	360	365	370	375	380
Maximum Power Voltage Vmp (V)	33.9	34.1	34.3	34.5	34.7
Maximum Power Current Imp (A)	10.62	10.71	10.79	10.87	10.96
Open Circuit Voltage Voc (V) <small>(tolerance±2%)</small>	40.90	41.10	41.30	41.50	41.70
Short Circuit Current Isc (A) <small>(tolerance±3%)</small>	11.23	11.32	11.41	11.49	11.58
Module Efficiency (%)	19.4%	19.7%	20.0%	20.2%	20.5%

STC: Irradiance 1000W/m², Cell Temperature 25°C, Air Mass AM1.5

NMOT: Irradiance at 800W/m², Ambient Temperature 20°C, Wind Speed 1m/s

REAR SIDE POWER GAIN (JT365SIh(B))

Power Gain	5%	10%	15%	20%	25%	30%
Maximum Power - Pmax (W)	383	402	420	438	456	475
Maximum Power Voltage -Vmp (V)	34.1	34.1	34.1	34.2	34.2	34.2
Maximum Power Current -Imp (A)	11.23	11.79	12.32	12.81	13.34	13.89
Open Circuit Voltage -Voc (V)	41.1	41.1	41.1	41.2	41.2	41.2
Short Circuit Current -Isc (A)	11.93	12.49	13.02	13.51	14.04	14.59

TEMPERATURE RATINGS

Temperature Coefficient of Isc (αIsc)	+0.05%/°C
Temperature Coefficient of Voc (βVoc)	-0.30%/°C
Temperature Coefficient of Pmax (γPmp)	-0.35%/°C
Normal Module Operating Temperature (NMOT)	41°C±3°C

OPERATING PARAMETERS

Maximum System Voltage	1500V/DC(IEC)
Operating Temperature	-40°C~+85°C
Maximum Series Fuse	20A
Maximum Test Load,Push/Pull	5400Pa/2400Pa
Conductivity at Ground	≤ 0.1Ω
Safety Class	II
Resistance	≥100MΩ
Voc and Isc Tolerance	±3%
Bifaciality	70±5%


MECHANICAL DATA

Solar Cell Type	Mono 83×166 mm(6 inches)
Number of Cells	120 [2 x (10 x 6)]
Module Dimensions	1773×1046×30 mm(69.8×41.2×1.2 inches)
Weight	24.5 kg(54 lb)
Front Cover	2.0 mm (0.08 inches), high transmission, AR coated tempered glass
Back Cover	2.0 mm (0.08 inches), high transmission, AR coated tempered glass
Frame	Silver, anodized aluminium alloy
J-Box	≥IP67
Cable	4.0 mm ² solar cable, 300 mm(11.8 inches)
Number of diodes	3
Connector	05-8, PV-JM608

PACKAGING CONFIGURATION

Module per pallet	35 pieces
Module per 40'HQ container	26 pallets, 910 pieces

DIMENSION



Remarks

*Installation instruction must be followed. See the installation manual or contact our technical service department for further information on approved installation.
 *The specification and key features described in this datasheet may deviate slightly and are not guaranteed. Due to ongoing innovation, R&D enhancement, Jetion Solar (China) Co., Ltd. reserves the right to make any adjustment to the information described herein at any time without notice. Please always obtain the most recent version of the datasheet which shall be duly incorporated into the binding contract made by the parties governing all transactions related to the purchase and sale of the products described herein. Jetion Solar_REV_2021_01_EN